



KEY

Fire proof construction.
 Semi fireproof construction.
 Hollow concrete or cement block construction.
 Brick building with brick or metal cornice.
 Brick veneered building.
 Brick and frame.
 Frame building.
 Stone building.
 Fire wall 6 inches above roof.
 Figures, 8 to 16, to indicate thickness of wall in inches.
 Wall without opening and size in inches.
 with openings, figures indicate on which floor.
 being protected by single iron or tin clad doors.
 wired glass doors.
 sliding iron vault doors.
 or standard tin clad doors.
 Windows protected by iron shutters.
 Windows with iron shutters.
 Windows opening in first story.
 second and third stories.
 fourth.
 Windows with wired glass.
 Windows 1st and 2nd with iron shutters,
 3rd and 4th with tin clad shutters, and
 wired glass.

Highways.
 Elevators.
 Stable.
 Frame enclosed elevator with traps.
 self closing traps.
 traps.
 self closing traps.
 wired glass doors.
 Steam boilers.
 Chimneys.
 Engine and horse power in figures.
 Water pipes and size in inches.
 Hydrants.
 Vertical pipe or stand pipe.
 with fire escape.
 Fire alarm box.
 Automatic sprinklers.
 Force pump.
 Elevation.
 Automatic fire alarm.
 Independent electric plant.
 Under sheet number refers to corresponding sheet of previous edition.
 Reference to adjoining sheet.
 Fire engine house, as shown in key map.
 Block number.

